

5.6" LCD Test Monitor

Features

- ▶ Lightweight & compact size
- ▶ Resolution 320x234 pixels
- ▶ NTSC/PAL auto recognition
- ▶ Two video BNC input and one audio jack input
- ▶ Test pattern generator (color bars/ cross hatch/ RGB/Dot)
- ▶ Multi-language support OSD
- ▶ Carrying strap and travel case
- ▶ Rechargeable battery and AC adaptor
- ▶ Anti-scratch & anti-reflectiveness visor
- ▶ Ideal for CCTV installation, on-site demonstration and testing
- ▶ Last memory for settings when powered off
- ▶ Power saving while no signal input




Specification		LV-56R01
Model		LV-56R01
LCD panel spec.	LCD display	Color 5.6" LCD
	Screen size(Viewable size)	5.6" (113.3 (H) × 84.7mm (V))
	Max. resolution	320(H) × 234 (V)mm (4:3)
	Lamp life time	20,000 hrs
	Dot pitch	0.118(H) × 0.362 (V)mm
	Contrast ratio	150:1 Typ.
	Brightness	300 cd/m ² (TYP.)
	Response time Tr/Tf	15/20ms (TYP.)
	Viewing angle L/R	45° / 45°
	Viewing angle Up/Down	10° / 30°
Front control		Power on/off, Power/Recharge LED indicator, SOURCE, Up(Volume Increase), Picture(OSD menu), Down(Volume Decrease)
Display mode		Video 1, Video 2, Test pattern
OSD menu	Video	Language, Auto Off, Contrast, Brightness, Color, Tint, Sharpness, Recall
Signal connector	Input	2 x BNC Inputs (1.0Vp-p 75Ω); 1 x Audio Input (3.5Ωstereo Jack)
	Output	1 x BNC Outputs (2.0Vp-p 75Ω); 1 x Audio Output (3.5Ωstereo Jack)
Audio speaker		1W (Max.)
Environment considerations	Operating condition	Temperature: 0°C ~ 40°C
	Storage Condition	Temperature: -20°C ~ 60°C
Power Input		AC Input :100 ~ 240V/1.5A, 50 / 60Hz
Power consumption		14W
Power Supply		DC 9V
Dimension	Net (WxHxD)	180 × 120 × 34mm
	Packing(WxHxD)(1pcs/Box)	256 × 175 × 116mm
	Weight	N.W.: 1.2kgs, G.W.: 1.6kgs
Stands / bracket supported		1/4" standard screw mount on bottom
Rechargeable battery		Li-Poly battery (7.4V / 2650mAh)
Safety		FCC, CE(EMC/LVD), UL, BSMI, CCC
Material	Front Panel	Plastic
	Rear Cover	Plastic
Optional accessories	Rechargeable battery	BT-088269

Specification subject to change without notice.

Accessories

Test Pattern Generator



Packing list

- ▶ 5.6" TFT LCD monitor x1
- ▶ Travel case with carrying and waist strap x1
- ▶ AC adaptor x1
- ▶ Rechargeable Li-poly battery x1
- ▶ 12VDC vehicle cigar lighter charger x1
- ▶ 3.5" stereo jack to RCA jack cable x1
- ▶ User manual x1

Dimension

