



Digital Signage LCD Monitor DR-19 Risc Series



| Model | | DR-19 |
|------------------------------|---------|---|
| LCD Display | | 19" active matrix TFT color LCD |
| Pixel pitch | | 0.294(H) X 0.294(V)mm |
| Max. Resolution | | SXGA1280 X 1024 (landscape) |
| Contrast Ratio | | 500:1 |
| Brightness | | 300 cd/m ² (typical) |
| Response Time (Tr+Tf) | | 8 ms (typical) |
| Display Color | | 16,777,216 colors |
| Active Area | | 376.32 x 301.056 mm |
| Viewing Angle (CR>10) | L/R | 170° (typical) |
| | U/D | 170° (typical) |
| Lamp Life Time | | 50,000 hrs |
| Signal Connector Input | Network | RJ-45 x 1 |
| | USB | USB type A connector x 2 |
| Scan Frequency | | H. scan 31~60KHz, V. scan 60~75H |
| Audio System | | 1W/per channel driver (option) |
| Key Control | | Power on/off, mode, up(contrast adjust), down (brightness adjust), Menu, auto, LED indicator, increase (volume increase), Decrease (volume decrease) |
| | | Brightness, contrast, H-position, V-position, clock, phase, color temp, User color-R, user color-G, User Color-B, OSD-H-position, OSD-V-position, volume, PIP, language, recall |
| | | Color, tint (NTSC only), brightness, contrast, sharpness, Volume, language, color temp, recall, Scan (1:1, under scan, over scan, full scan, 4:3, 16:9), PIP, H-position |
| OSD Functions: PC | | |
| OSD Functions: Video | | |
| Features | | 3D comb filter (NTSC/PAL video) |
| | | VESA 100 mounting hole x 2 |
| | | PIP and POP for multi-screen arrangement |
| Optional | | Built-in internal storage with 40GB hard disk drive |
| Power Input | | Input AC 100~240V, 50~60Hz; output DC 18V / 3.9A |
| Power Consumption | | 50W (Typ.) |
| Power Management | | VESA DPMS standard |
| Operating Temperature | | 0°C-40°C (32°F-104°F) |
| Conditions Humidity | | 10%-85% (no condensation) |
| Altitude | | To 10,000 feet |
| Storage Temperature | | -20°C-60°C (-4°F-140°F) |
| Conditions Humidity | | 10%-85% (no condensation) |
| Dimensions | | 590(W) x 405(H) x 45(D) mm |
| Dimensions (Carton) | | TBD |
| Weight including stand (Net) | | TBD |
| Certification | | CE, FCC, UL/C-UL, CCC, BSMI |

- Risc core media player system
- Content-rich presentation: plays video, audio, graphics, and text
- Updates contents & scheduling over network without disturbing foreground display
- Multiple display zones for maximum advertising efficiency
- Flexible scheduling capability
- Supports MPEG 1/2/4 and DivX 5.0 video format; JPEG and BMP graphics
- Supports 16:9 and 4:3 display in landscape or portrait mode
- Supports HDTV resolution; automatically scales up SD content to HD output
- Automatic Play-On-Power-Up
- Built-in internal storage with 40GB hard disk drive (Optional)
- Wireless LAN support via external Wi-Fi solution
- Adaptive 3D comb filter for life like and sharp images
- IR remote control
- High color saturation
- Multi-language OSD
- VESA 100 mounting hole x 1
- Multiple mounting solutions provided

Unit:mm

Specification is subject to change without notice. 2008. 04



TAIWAN VIDEO SYSTEM CO., LTD.

8F-2., No.188, Sec.3, Tatung Rd., Hsi-tze,
Taipei, Taiwan, R.O.C. 221
Tel: 886-2-86473637 Fax: 886-2-86473627
http://www.tvs.com.tw E-mail: info@tvs.com.tw

TVS GROUP

USA TVSA e-mail: info@eversun.com
Germany TVSG e-mail: info@tvsg.de
China TVSC e-mail: info@tvsc.com.cn

