

POS SYSTEM

Your PASS key to POSSibility

- Flat Series

- Spill-proof architecture and easy cleaning
- Security lock prevents unauthorized access to storage device
- Easy to maintain and service without using screwdriver to reach key components
- Your best choice for P.O.S. kiosk, point of service... etc.
- Optional touch screen or strengthen glass for primary display





POS SYSTEM

Your PASS key to POSSibility



FP-1512/1510

Flat Series

FP-1500

- Spill-proof architecture and easy cleaning
- Security lock prevents unauthorized access to storage device
- Easy to maintain and service without using screwdriver to reach key components
- Your best choice for P.O.S. kiosk, point of service... etc.
- Optional touch screen or strengthen glass for primary display



FP-1512/1510 Side View



FP-1500 Side View



Customer-Side View (VFD)



FP-1520

Mode No.	FP-1500	FP-1512	FP-1520
Main Board			
CPU	Mobile Intel® Celeron® M Processor 1.2GHz		
Core Logic	Intel® 852GM Chipset / ICH4		
Display Chip	4X AGP LCD/VGA controller advance hardware 2D/3D GUI engine Sharing memory architecture up to 64MB		
System Memory	1 x 184 pin supporting DDR up to 1GB		
L2 cache	CPU built-in		
Display			
TFT LCD	Main Display	15"	
	2nd Display	None	12.1" 20 columns x 2 lines VFD
Resolution	1024x768	1024x768(15") & 800x600(12.1")	—
Touch Screen	Resistive Type for Main Display only		
Expansion			
mini PCI	Slot x 1		
Compact Flash	Type II Slot x 1		
I/O Ports			
Rear-end	Serial	Series ports x 4, COM 1, 2&4 with +5/12V power output on pin 9, COM 3 is internal type reserved for touch screen, optional COM 5	
	Parallel	1 (SPP/EPP/ECP)	
	USB	USB 2.0 x 2	
	PS2 Mouse/Keyboard	1	
	LAN	RJ45, 10/100 Base-T x1	
	VGA	1	
	Cash Drawer	RJ11 with 12V output	
	Audio Jack	MIC-in, Speaker-out	
Front-end	USB	USB2.0 x 2	
	Dallas i-Button Key	Dallas i-Button Key x 1 (optional)	
Dimension			
H30.2 x W36.5 x D40 (FP-1512) / H30.2 x W36.5 x D35.7 (FP-1500)			
Others			
Internal Speaker	1W x 2		
Stand	Tilt angle: 15°~90°		
Power Supply	ATX 120W, (input range: 100~240V)		
Operating Temperature	0 ~ 40°C		
Optional			
Card Reader	3 Tracks approx 300,000 passes		
HDD	EIDE 3.5" Type		
CD-ROM	Slim Type		
Memory	DDR RAM		
Color	Black		

Specification subject to change without notice.