

POS SYSTEM

Your PASS key to POSSibility
- Tower Series



- Spill-proof architecture and easy cleaning
- Special design for heat dissipation
- Tilt angle adjustable for LCD monitor from 0° to 45°
- Security lock prevents unauthorized access to storage device
- Your best choice for P.O.S. kiosk, point of service... etc.
- Optional touch screen or strengthened glass for primary display



Flat Series

POS SYSTEM

Your PASS key to POSSibility

- Spill-proof architecture and easy cleaning
- Special design for heat dissipation
- Tilt angle adjustable for LCD monitor from 0° to 45°
- Security lock prevents unauthorized access to storage device
- Your best choice for P.O.S. kiosk, point of service... etc.
- Optional touch screen or strengthen glass for primary display



TP-1500 Side View







TP-1512 Side View
(Recommended)



Customer-Side View
Strengthen glass applied on 2nd LCD display from outside damage

Mode No.	TP-1500	TP-1512
Main Board		
CPU	Mobile Intel® Celeron® M Processor 1.2GHz	
Core Logic	Intel® 852GM Chipset / ICH4	
System Memory	1 x 184 pin supporting DDR up to 1GB	
L2 cache	CPU built-in	
Display		
TFT LCD	Main Display	15"
	2nd Display	None 12.1
Resolution	1024 x 768	1024x768(15") & 800x600(12.1")
Touch Screen	Resistive Type for Main Display only	
Expansion		
mini PCI	Slot x 1	
Compact Flash	Type II Slot x 1	
I/O Ports		
Rear-end	Serial	3 x COM (Pin 9 with 5/12V Selected)
	Parallel	1 (SPP/EPP/ECP)
	USB	12V Powered USB x1 24V Powered USB x1
	PS2 Mouse/Keyboard	1
	LAN	RJ45, 10/100 Base-T x1
	VGA	1
	Cash Drawer	RJ11 (Power Pin 12/24V Selectable) x1
Front-end	Audio Jack	MIC-in, Speaker-out
	USB	USB2.0 x 2
	Smart Card Reader	PC/SC, ISO-7816, CCID specification
Others		
Internal Speaker	1W x 2	
Power Supply	ATX 120W, (input range: 100~240V)	
Operating Temperature	0 ~ 40°C	
Optional		
Card Reader	3 Tracks approx 300,000 passes	
HDD	EIDE 3.5" Type	
CD-ROM	Slim Type	
Memory	DDR RAM	
Color	Black or White	

Dimension



Unit:mm

Specification is subject to change without notice. 2008.01



TAIWAN VIDEO SYSTEM CO., LTD.

8F-2., No.188, Sec.3, Tatung Rd., Hsi-tze,
Taipei, Taiwan, R.O.C. 221
Tel: 886-2-86473637 Fax: 886-2-86473627
http://www.tvs.com.tw E-mail: info@tvs.com.tw

TVS GROUP

USA TVSA e-mail: info@eversun.com
Germany TVSG e-mail: info@tvsg.de
China TVSC e-mail: info@tvsc.com.cn

